
# GASSAVA

Production, Processing and Utilization in Nigeria





FEDERAL INSTITUTE OF INDUSTRIAL RESEARCH, OSHODI, (FIIRO)

ECONOMIC VIABILITY OF CASSAVA PROCESSING INTO FUFU

BY

MRS. B.O. OYEDOYIN (MRS.)

A CONTRIBUTION TO THE BOOK TITLED; CASSAVA PRODUCTION, PROCESSING AND UTILIZATION

## ECONOMIC VIABILITY OF CASSAVA PROCESSING INTO POWDERED FUFU

## Production Programme

The production schedule adopted for production of Fufu is based on a number of criteria, which include.

- The extent of the market for the finished product
- The capabilities of available production plants and their efficiency
- The skill and efficiency of the labour force and
- The availability of raw materials. The proposed production schedule of Fufu as follows: -

## A. Number of hours, shift working days

No. of hours per shift	8
No. of shifts/day	2
No. of working days/week	5
No. of working days/year	250

## B. Quantity of Fufu produced

C.	Input; output Ratio	18% i.e. 5.5:1
	Output of Fufu per year	500 Tones
	Output of Fufu per day	2tonnes
	Output of Fufu per shift	1 Ton

RAW MATERIALS SUPPLIES UTILITIES REQUIREMENTS.

### Requirements:

These are the same required as for Gari processing

FACTORY SPACE REQUIREMENT

The same amount of floor area is required as for Gari production

PERSONNEL REQUIREMENT.

The same amount of floor area is required as for Gari production

#### PROPOSED PRODUCTION PROGRAMME

Maximum capacity utilization is proposed to be achieved at 80% for the first year and 90% in subsequent years. Two shifts are recommended from second years

capacity utilization is lower to allow the factory workers gain experience on the job and also allow for the market penetration of the product. The total production at 100% capacity utilization is 250 tonnes in the first year of 1 shift. The total production at 100% capacity 500 tonnes from in the second year of 2 shifts.

## The proposed production programme can be summarized.

Year	1	2 - 5	
Capacity utilization shift	80%	90%	
Annual output (tones)	200	450	

## LIST AND ESTIMATED COST OF PROCESSING MACHINERY AND EQUIPMENT FOR 2 TONS/DAY FUFU PRODUCTION

S/N	ITEM	ESTIMATED COST (N)
1.	Continuous Pulping and sifting machine	180,000.00
2.	Hydraulic press steel	180,000.00
3.	Fermentation tank (tilled concrete type)	70,000.00
4.	Cake Granulator	170,000.00
5.	Flash Dryer (2.5T/Day)	3,000,000.00
6.	Shaker Screen	210,000.00
7.	Dry mill (Hammer mill)	170,000.00
8.	Double Cone Mixer	150,000.00
9.	Heat Sealer	25,000.00
10.	Bag Stitcher	30,000.00
11.	Weighing Machine	85,000.00
	- raw materials	
	- finished product	•
12.	Accessories	
	(plastic troughs 10	5,000.00
	- Peeling knives 10	5,000.00
		4,280,000.00
	and the same of th	V

## ESTIMATED INITIAL FIXED COST FOR GARI

TOTAL	10,108,000.00
Utility vehicle (fairly used prick -up van)	1,200,000
Generator (60 KVA) (used)	650.000.00
Borehole, Water tank, Pipes, pump	300.000.00
Furniture and fittings	1,000,000.00
Machinery & Equipment including installation and commissioning	4,708,000.00
Factory Building	2000.000.00
Land (2 Plots)	250.000.00
Items	Cost (N)

## FACTORY SPACE REQUIREMENT

The floor area requirement is estimated at 40 square meters. The factor floor area may be divided into four main areas; the cassava arrival and preparation area, the fermentation area, main processing area and the product finishing area.

## PERSONNEL REQUIREMENTS.

CATEGORY A: (ADMIN)	NO	QUALIFICATION	ANNUAL ENUMERATION (N) ,
General Manager	1	Bsc/HND	360,000
Accounting officer	1	SSCE	120.000
Purchasing officer	1	SSCE	120.000
Sales/invoice officer	1	SSCE	120,000
Driver	1	FSLC	120.00
Security Guards	2	FSLC	168,00

## CATEGORY B: FACTORY PERSONNEL

Production Supervisor	1	OND	240,000	
Maintenance Technician	1	Trade Test	120,000	
Operative	4	FSLC	-336,000	
Factory Hands	6		288,000	
			N1, 992,000	

ECO	NOMIC VIABILITY FOR FUFU FLOUR PRODUC	TION (N)
(i)	Initial Fixed Capital Cost	10,108,000.00
(ii)	Initial Working Capital Cost	4,160,558.00
(iii)	Pre-production Expenses	779,459.00
(iv)	Pay-back Period (PBP)	1 years 4 months
$(\vee)$	Internal Rate of Return (IRR) is estimated at	above 50%
(vi)	Break - even (Volume:) -The Break - even volume	ne is estimated at about
	57,3372kg of Fufu powder i.e. 28.68% of annual	production during the of
	1 <sup>st</sup> year of shift per day at 72 days of production.	
(vii)	Rate of Return on Investment (RRI)	64.69%
(viii)	Net Present Value (NPV) at 30% is	25, 562, 660

Two main categories of personnel are identifies for the project. These are administrative personnel constitute the indirect labour force, while the factory staff constitute the direct labour force.

The administrative personnel required include;

- General Manager
- Accounting officer
- Purchasing officer
- Sales officer
- Security guards and Driver.

The factor personnel required include;

- Production supervisor
- Maintenance Technician
- Factory operatives and factory hands.

The no. of personnel required for the two shifts of 2 tonnes per 8-hour day is twenty (20). The General manager overseas and supervises the general running of the project and has the overall control over all labour. The accounting officer should have a minimum qualification of ordinary National Diploma (OND) records and keeps the company accounts and takes care of the financial affairs of the company such as staff salaries and monitoring of funds disbursement.

The purchasing officer who should have a minimum of ordinary National Diploma in purchasing and supplied with at least three years working experience. He is to

## PERSONNEL REQUIREMENTS.

CATEGORY A: (ADMIN)	NO	QUALIFICATION	ANNUAL ENUMERATION (N)
General Manager	1	Bsc/HND	360,000
Accounting officer	1 -	SSCE	120.000
Purchasing officer	1	SSCE	120.000
Sales/invoice officer	1	SSCE	120,000
Driver	1	FSLC	120.00
Security Guards	2	FSLC	168,00
CATEGORY B: FACTORY	Y PERS	ONNEL	
Production Supervisor	1	OND	240,000
Maintenance Technician	1	Trade Test	120,000
Operative	4	FSLC	336,000
Factory Hands	6		288,000
			N1, 992,000

food technology and should have at least three years working experience. He is directly responsible for the General Manager and the factory operative are

responsible to him. The factory operatives who should have a minimum of city and gauds certification should be skilled enough to operate the processing machine.